



*Prestige Viru*  
 MINI SPLIT INVERTER

- High Efficiency
- Voltage Protection
- Quiet Operation
- Turbo Cooling
- Wi-Fi Ready
- 3D Air Flow
- Coated PC Board



**Key Features**



**Coated PC Board**



**Low Voltage Starter**



**High Voltage Safety**



**Turbo Cooling**



**Quiet Operation**



**Self-Diagnostic**

MODEL		KIN310C2V31M	KIN413C2V32M	KIN321C2V31M	KIN824C2V31M	KIN930C2V31M	
SYSTEM	<b>CAPACITY</b>	BTU/H	9,000	12,000	18,000	24,000	30,000
		Range (BTU/H)	3,000 ~ 10,000	4,000 ~ 13,000	5,500 ~ 21,000	8,000 ~ 24,000	9,000 ~ 30,000
	<b>EFFICIENCY</b>	SEER	18.0	18.0	18.0	18.0	18.0
		Volt / Hertz	208~230V / 60Hz	208~230V / 60Hz	208~230V / 60Hz	208~230V / 60Hz	208~230V / 60Hz
	<b>ELECTRICAL</b>	Rated Current (A)	3.8	4.7	7.5	8.5	11.2
		Max Current (A)	15	15	25	25	30
	<b>OPER. AMBIENT TEMP.</b>	°F (°C)	64.4°F~109.4°F	64.4°F~109.4°F	64.4°F~109.4°F	64.4°F~109.4°F	64.4°F~109.4°F
	<b>APPLICATION AREA</b>	(Ft²)	170 ~ 220	200 ~ 270	300 ~ 390	350 ~ 470	450 ~ 625
	<b>MOISTURE REMOVAL</b>	Liter/Hr	0.8	1.2	1.5	2.2	2.8
	<b>REFRIGERANT</b>	R410A (g)	700	950	980	1600	2400
<b>REFRIGERANT CONNECTIONS</b>	Liquid (in)	1/4"	1/4"	1/4"	1/4"	1/4"	
	Suction (in)	3/8"	3/8"	1/2"	5/8"	5/8"	
	Maximum Length (Ft)	100	100	100	100	100	
	Maximum Height (Ft)	65	65	65	65	33	
INDOOR UNIT	<b>AIR FLOW</b>	CFM	380	450	700	950	950
	<b>MOTOR</b>	RPM (H-M-L)	1250/1200/950	1250/1200/950	1250/1200/950	1300/1140/850	1300/1140/850
	<b>FAN</b>	Type	THERMO-PLASTIC SCROLL FAN				
	<b>SOUND LEVEL</b>	dB(A) (H-M-L)	41 / 33 / 27	42 / 35 / 29	45 / 40 / 36	49 / 42 / 38	52 / 44 / 39
	<b>CONTROL</b>	Remote Control	LCD WIRELES REMOTE CONTROL or WIFI (Optional)				
		Auto Restart	YES				
		Protection	TIME DELAY				
	<b>INDOOR DIMENSIONS</b>	Unit W x H x D (in)	31 ¼ x 8 x 10 ¾	33 ¼ x 8 ¼ x 11 ¾	38 ¼ x 8 ¾ x 11 ¾	42 ¾ x 12 ½ x 9 ¼	53 ¼ x 10 x 12 ¾
		Package W x H x D (in)	34 ¼ x 10 ½ x 14 ¼	36 ¼ x 11 x 15	41 x 12 ¾ x 15	46 x 15 ½ x 12 ½	56 ¾ x 14 ½ x 16 ½
	<b>INDOOR WEIGHT</b>	Net / Gross (LBs.)	20 / 25	24 / 29	29 / 35	36 / 46	41 / 53
OUTDOOR UNIT	<b>AIR FLOW</b>	CFM	950	950	1850	1850	2350
	<b>COMPRESSOR</b>	RLA	4.1	5.1	8.1	8.95	11.5
		LRA	-	-	-	-	-
	<b>OUTDOOR SOUND LEVEL</b>	dB(A)	53	53	55	58	60
	<b>OUTDOOR DIMENSIONS</b>	Unit W x H x D (in)	30 ½ x 21 ¼ x 12 ¾	30 ½ x 21 ¼ x 12 ¾	37 ½ x 27 ½ x 15 ½	37 ½ x 27 ½ x 15 ½	39 x 31 x 17
		Package W x H x D (in)	32 ½ x 23 ½ x 13 ½	32 ½ x 23 ½ x 14	40 ½ x 18 x 29 ½	40 ½ x 29 ½ x 18	42 ¾ x 33 ¾ x 19 ½
<b>OUTDOOR WEIGHT</b>	Net / Gross (LBs.)	62 / 71	68 / 74	92 / 103	102 / 113	152 / 165	

\*Specifications are subject to changes without notice. \*\* Model numbers, pictures, and specifications of all products are subject to change without further notice.



### ACCESSORIES INCLUDED

- 3 Meter Copper
- Inter-connecting cable kit
- Installation Manual
- Plastic cover for valves
- LCD Wireless remote control



### PERFECT APPLICATION FOR



HOUSE



STORE



OFFICE

Distributed by :